

GRAPHICS - INK-JET DIGITAL

 Issue date : 03/03/2016
 Date last modification : 20/03/2019

4-GL3B-09279 RI-JET DECO WALL 150 LINEN AP940 PERMANENT WK135
Face Material

White satin finish polymeric PVC film with a linen pattern.

Type	Polymeric vinyl	
Colour and Finish	Linen pattern white satin finish	
Weight	172 g/m ² ±10%	ISO-536
Thickness	150 μ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP940 permanent	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-30°C/+120°C	
Shear	Medium	
Tack	7 N/inch ²	
Final Adhesion	9 N/inch	

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	135 g/m ² ±10%	PP-032 - ISO 536
Thickness	145 μ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

For interior wall decoration.

This PVC self-adhesive material offers a cost effective solution to interior designers who are looking for a film to internal walls or shop interiors.

Application method: apply to clean, flat dust free surfaces. It is recommended to prime fresh plaster prior to application.

Product designed to give permanent bond to most wall substrates, including painted, plasterboard, primed plaster, etc.

1,5 cm overlapping recommended.

. Flammability: Self - extinguish (ISO-3795)

. Outdoor vertical exposure durability: UP TO 5 YEARS.

The Durability data are given for unprinted films only and based on Zone 1 exposure conditions (Northern and Eastern Europe, Italy, France).

Printing Methods

Printable with solvent, eco-solvent and UV ink-jet.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

 24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.