


# INCREASE VISIBILITY IN LOW-LIGHT CONDI-TIONS, DIN 20471 CERTIFIED.

Reflective heat transfer material is thin, economical with a reflective finish. This material has a no-tack backing and is easy to cut and



## **AVAILABLE IN**

50 cm x 25 m rolls

### RECOMMENDED FABRICS

- 100% cotton
- 100% polyester\*
- · Polyester-cotton blends
- \* Test before application!

## **IMPORTANT**

Please remove the protection carrier before cutting.

#### CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 3 mm for lettering and logos.

## APPLICATION INSTRUCTIONS

Temperature: 150° C

Time: 5 sec. Repressing 5 sec.

• Pressure: medium (#4-6 on Hotronix®) Peel: warm-cold

# MULTI-COLOR DESIGNS

CAD-CUT® Reflective is not suitable for mulit-layer application.

# ACCESSORIES RECOMMENDED

- · Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®

## CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry clean. Iron only inside out.

### **STORAGE**

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

#### **DETAILS**







Easy weed





Ironable



Ironable only inside out



Washable



Sublimation



Stretchable



Flock





Thin



Sticky carrier Multi-color



application Peel hot







# **CAD-CUT® REFLECTIVE**





