
# **CAD-CUT®** SOFT METALLIC

# SOFT METALLIC HEAT TRANSFER MATERIAL FEATURES A DISTINCT LUSTER AND SHINE

Creates a soft, metallised finish for textile decoration. It is supplied on a self-adhesive polyester carrier



63

#### AVAILABLE IN

50 cm x 10 m rolls

#### RECOMMENDED FABRICS

- 100% cotton
- 100% polyester
- Polyester-cotton blends blends
- \* Test before application!

## CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For opti-mal cutting and weeding, maintain a line thickness of at least  $1.5 \text{ mm} (1/16^\circ)$  for lettering and logos.

## APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 10 sec.
- Pressure: medium
- (#4-6 bei Hotronix<sup>®</sup>)
- Peel: cold

## MULTI-COLOR DESIGNS

Apply background for 2-4 seconds, peel carrier warm/cold. Repeat for additional colors. Finish with final application of 13-15 seconds. Peel cold.

#### ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder<sup>®</sup>, LED Weeder. LED Pin or Tweezers

## CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Do not dry-clean. Do not iron directly onto CAD-CUT® Soft Metallic (use cover sheet).

#### STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

#### DETAILS









# **CAD-CUT®** SOFT METALLIC



